



Release 177 Graphics Drivers ***Release Notes***

Version 177.41

**For Windows Vista 32-bit
and Windows Vista 64-bit**

**NVIDIA Corporation
June 26, 2008**

Published by
NVIDIA Corporation
2701 San Tomas Expressway
Santa Clara, CA 95050

Notice

ALL NVIDIA DESIGN SPECIFICATIONS, REFERENCE BOARDS, FILES, DRAWINGS, DIAGNOSTICS, LISTS, AND OTHER DOCUMENTS (TOGETHER AND SEPARATELY, "MATERIALS") ARE BEING PROVIDED "AS IS." NVIDIA MAKES NO WARRANTIES, EXPRESSED, IMPLIED, STATUTORY, OR OTHERWISE WITH RESPECT TO THE MATERIALS, AND EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES OF NONINFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE.

Information furnished is believed to be accurate and reliable. However, NVIDIA Corporation assumes no responsibility for the consequences of use of such information or for any infringement of patents or other rights of third parties that may result from its use. No license is granted by implication or otherwise under any patent or patent rights of NVIDIA Corporation. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. NVIDIA Corporation products are not authorized for use as critical components in life support devices or systems without express written approval of NVIDIA Corporation.

Trademarks

NVIDIA, the NVIDIA logo, 3DFX, 3DFX INTERACTIVE, the 3dfx Logo, STB, STB Systems and Design, the STB Logo, the StarBox Logo, NVIDIA nForce, GeForce, NVIDIA Quadro, NVDVD, NVIDIA Personal Cinema, NVIDIA Soundstorm, Vanta, TNT2, TNT, RIVA, RIVA TNT, VOODOO, VOODOO GRAPHICS, WAVEBAY, Accuviv Antialiasing, the Audio & Nth Superscript Design Logo, CineFX, the Communications & Nth Superscript Design Logo, Detonator, Digital Vibrance Control, DualNet, FlowFX, ForceWare, GIGADUDE, Glide, GOFORCE, the Graphics & Nth Superscript Design Logo, Intellisample, M-BUFFER, nfiniteFX, NV, NVChess, nView, NVKeystone, NVOptimizer, NVPinball, NVRotate, NVSensor, NVSync, the Platform & Nth Superscript Design Logo, PowerMizer, Quincunx Antialiasing, Sceneshare, See What You've Been Missing, StreamThru, SuperStability, T-BUFFER, The Way It's Meant to be Played Logo, TwinBank, TwinView and the Video & Nth Superscript Design Logo are registered trademarks or trademarks of NVIDIA Corporation in the United States and/or other countries. Other company and product names may be trademarks or registered trademarks of the respective owners with which they are associated.

Intel, Indeo, and Pentium are registered trademarks of Intel Corporation. Microsoft, Windows, Windows NT, Windows Vista, Direct3D, DirectDraw, and DirectX are trademarks or registered trademarks of Microsoft Corporation. OpenGL is a registered trademark of Silicon Graphics Inc. PCI Express, PCI-SIG, and the PCI-SIG design marks are registered trademarks and/or service marks of PCI-SIG. DisplayPort is a trademark of the Video Electronics Standards Association (VESA).

Other company and product names may be trademarks or registered trademarks of the respective owners with which they are associated.

Copyright

© 2008 by NVIDIA Corporation. All rights reserved.



Table of Contents



1. Introduction to *Release Notes*

Structure of the Document	1
Changes in this Edition	1

2. Release 177 Driver Changes

Version 177.41 Highlights	4
What's New in Release 177	4
What's New in Version 177.41	4
Limitations in This Release.	5
Changes in Version 177.41	6
Fixed Issues—Windows Vista 64-bit	6
Open Issues in Version 177.41	7
Windows Vista 32-bit Issues	7
Windows Vista 64-bit Issues	7
Not NVIDIA Issues	8
Windows Vista Limitations	8
Unsupported Features	9
OpenGL Application Issues	11
Application Issues	12
Operating System Issues	13

3. The Release 177 Driver

Hardware and Software Support	15
Supported Operating Systems	15
Supported NVIDIA Products	16
Supported Languages	16
Driver Installation	17
Minimum Hard Disk Space	17
Before You Begin.	17
Installation Instructions.	17
NVIDIA Driver History	18
Known Product Limitations	20
Image Sharpening Control not Available with GeForce 8 Series and later GPUs	20
Gigabyte GA-6BX Motherboard	20

A. Mode Support for Windows

General Mode Support Information	22
Default Modes Supported by GPU	23
Understanding the Mode Format.	23
GeForce 200 Series of GPUs	24
nForce 7xx Series	26
Modes Supported by TV Encoders	29



List of Tables



Table 3.1	Supported NVIDIA Products	16
Table 3.1	NVIDIA Drivers for Windows Vista	18
Table A.1	Modes Supported for High Resolution Displays	22
Table A.2	Non-standard Modes Supported	22
Table A.3	Mode Support for S-Video and Composite Out	29
Table A.4	Mode Support for Component YPrPb Out and DVI Out	29

CHAPTER

1

INTRODUCTION TO *RELEASE NOTES*

This edition of *Release Notes* describes the Release 177 Graphics Drivers for Microsoft® Windows® Vista. NVIDIA provides these notes to describe performance improvements and bug fixes in each documented version of the driver.

Structure of the Document

This document is organized in the following sections:

- “[Release 177 Driver Changes](#)” on page 3 gives a summary of changes, and fixed and open issues in this version.
- “[The Release 177 Driver](#)” on page 15 describes the NVIDIA products and languages supported by this driver, the system requirements, and how to install the driver.
- “[Mode Support for Windows](#)” on page 21 lists the default resolutions supported by the driver.

Changes in this Edition

This edition of the *Release Notes* for Windows Vista includes information about NVIDIA graphics driver version 177.41, and lists changes made to the driver since version 175.19. These changes are discussed beginning with the chapter “[Release 177 Driver Changes](#)” on page 3.

CHAPTER

2

RELEASE 177 DRIVER CHANGES

This chapter describes open issues for version 177.41, and resolved issues and driver enhancements for versions of the Release 177 driver up to version 177.41. The chapter contains these sections:

- “Version 177.41 Highlights” on page 4
- “Changes in Version 177.41” on page 6
- “Open Issues in Version 177.41” on page 7
- “Not NVIDIA Issues” on page 8
- “Known Product Limitations” on page 20

Version 177.41 Highlights

This section provides highlights of version 177.41 of the NVIDIA Release 177 Driver for Windows Vista.

- [What's New in Release 177](#)
- [What's New in Version 177.41](#)
- [Limitations in This Release](#)

What's New in Release 177

- Added support for the following NVIDIA products:
 - GeForce GTX 280
 - GeForce GTX 260
 - nForce 780a SLI
 - nForce 750a SLI
- Added support for hot-plug detection of VGA displays that provide EDID information.
- Added support for DDC-Ci/MCCS over the DisplayPort AUX channel.
- Added the NVIDIA Control Panel option to expose only consumer electronics (CE) resolutions for HDMI inputs.

What's New in Version 177.41

- Added support for the following NVIDIA products:
 - GeForce GTX 280
 - GeForce GTX 260
 - nForce 780a SLI
 - nForce 750a SLI
- See [“Changes in Version 177.41”](#) on page 6 for a list of resolved issues.

Limitations in This Release

The following are features that are not currently supported or have limited support in this driver release:

- **NVIDIA SLI Antialiasing**
- **INF Support for Restricted Timings**

This driver version does not support the use of Restricted Timing settings (R&T strings) in the INF to control mode validation and/or mode setting for custom mode/adaptor/monitor combinations. This capability is planned for a later driver release.

NVIDIA Control Panel features that are Not Yet Available

Support for the following control panel features is under development and not yet available under Windows Vista:

- **Display Category**
 - The Graph tab on the Adjust Desktop Color Settings page is not available.

Changes in Version 177.41

The following sections list the changes made and issues resolved since driver version 177.35.

- “Fixed Issues–Windows Vista 64-bit” on page 6

The NVIDIA bug number and driver module are provided for reference.

Fixed Issues–Windows Vista 64-bit

Multi-GPU Issues

- [SLI]: Program settings cannot be applied for a newly added SLI profile if the profile duplicates an existing one. [393649]
- [SLI], GeForce GTX 280/260: Medusa demo (DirectX 10) - the demo flickers when the character starts turning into stone, during the glow effect. [434883]

Open Issues in Version 177.41

As with every released driver, version 177.41 of the Release 177 driver has open issues and enhancement requests associated with it. This section includes lists of issues that are either not fixed or not implemented in this version. Some problems listed may not have been thoroughly investigated and, in fact, may not be NVIDIA issues. Others may have workaround solutions.

- [“Windows Vista 32-bit Issues”](#) on page 7
- [“Windows Vista 64-bit Issues”](#) on page 7

Windows Vista 32-bit Issues

Single GPU Issues

All GPUs

- The graphics driver installer sometimes displays an ‘incorrect operating system’ error message when trying to install on a GPU that not supported by the driver. [310188]
- Counter Strike—the application crashes to the desktop if the resolution or bit-depth is changed from the in-game video options menu.

The problem does not occur if you change the resolution or bit-depth from the game’s main menu and not while in a game.

Multi-GPU Issues

- [3-way SLI], GeForce GTX 280/260: The 3-way SLI visual indicator flickers when running an OpenGL application. [439446]

Windows Vista 64-bit Issues

Single GPU Issues

- GeForce GTX 280/260: Half Life 2: Episode 2—in-game brightness is greatly reduced if Enhanced or Override AA is enabled from the NVIDIA Control Panel. [429254]

Not NVIDIA Issues

This section lists issues that are not due to the NVIDIA driver as well as features that are not meant to be supported by the NVIDIA driver for Windows Vista.

- “Windows Vista Limitations” on page 8
- “Unsupported Features” on page 9
- “OpenGL Application Issues” on page 11
- “Application Issues” on page 12
- “Operating System Issues” on page 13

Windows Vista Limitations

These are behaviors that may be different from Windows XP and are related directly to the Windows Vista operating system.

- **NVIDIA TurboCache**

Windows Vista now controls the allocation of system memory to the GPU for TurboCache functions. The Windows Vista Display Properties pages show the shared system memory (SSM), or how much memory is allocated for NVIDIA GPUs to use for TurboCache.

For more information on graphics memory reporting under Windows Vista, visit <http://www.microsoft.com/whdc/device/display/graphicsmemory.mspx>.

Unsupported Features

The following are features and functionality that were available in driver releases supporting Windows XP, but are not—and will not be—available in driver releases for Windows Vista:

- **High resolution scaling desktop (HRSD)**
- **MultiView Display Mode** (for NVIDIA Quadro NVS graphics cards)
- **NVKeystone**
- **Unified back buffer (UBB) controls**
- **OpenGL Video Overlays**

This is an operating system limitation.

Vista window manager features will provide new ways of accomplishing overlays, but will require application porting.

- **Overclocking**

GPU overclocking is no longer supported in the default GPU driver control panel. This feature is available in the NVIDIA System Tools software, which you can download from NVIDIA.com.

- **GPU Temperature Monitoring**

Temperature monitoring is no longer supported in the default GPU driver control panel. This feature is available in the NVIDIA System Tools software, which you can download from NVIDIA.com.

- **AGP Settings Adjustment**
- **Full-screen Video Mirror**
- **Video Zoom**

- **Pan & Scan** - the process of panning across the desktop in order to display a desktop on a monitor with lower resolution

- **Per-display Desktop Color Setting Adjustments**

For Clone mode, the desktop color setting adjustments through the NVIDIA Control Panel can only be made across all displays in a system, and not on a per-display basis.

- **Per-display Video Color Setting Adjustments**

For Dualview mode, the video color setting adjustments through the NVIDIA Control Panel can only be made across all displays in a system, and not on a per-display basis.

- **Edge Blending**
- **Run display optimization wizard**

- **Run multiple display wizard**
- **Run television setup wizard**
- **nView Horizontal and Vertical Span Modes**

Due to architectural changes in the new Windows Vista Window Display Driver Model (WDDM), span mode cannot be supported in NVIDIA graphics drivers. NVIDIA recommends using the built-in Windows Vista multi-display modes.

- **Display/Connection Wizard** (such as was provided with Windows Media Center Edition)
- **DVD/MPEG Extensions** (such as was provided with Windows Media Center Edition)
- **Audio Extensions** (such as was provided with Windows Media Center Edition)
- **Windowed quad-buffered stereo**

This is an operating system limitation.

- **NVIDIA nView Desktop Manager**

The nView Desktop Manager will not be included in drivers for GeForce products.

OpenGL Application Issues

The following are known compatibility issues for OpenGL applications developed under Windows XP:

- Mixed GDI and OpenGL rendering does not work.

A number of applications use GDI to render UI components and object highlighting. This is not supported in the Windows Vista driver model.

NVIDIA recommends converting GDI rendering to OpenGL.

The following are some applications that are known to have this issue:

- Maya 7.01
- OneSpace Designer Modeling
- Applications, Tools, and Benchmarks not Supported Under Windows Vista
 - GLperf
 - 3ds max 8 (later releases may be supported)
 - CATIA V5R15 (V5R16 is supported)
 - PTC's CDRS 2001
- Front buffered rendering may be slow, especially when DWM is enabled.

Flushing the rendering queue while rendering to the front buffer may cause the window manager to recomposite. Applications should therefore minimize the frequency with which they flush the rendering queue.

Application Issues

- Star Wars: Knights Of The Old Republic 2—the game fails to launch, and an “application has stopped working” error message appears. [420115]
This occurs because the application is not able to interpret the driver version correctly.
- Tiger Woods PGA Tour 2007—Fly-by shot before each hole blacks-out textures. [274697]
NVIDIA is working with the developer to resolve this issue.
- City of Heroes—The mouse cursor does not display. [259256]
*This is an application issue that can be worked around in full-screen mode by adding “compatiblecursors 1” to the City of Heroes desktop shortcut.
NVIDIA is pursuing a fix with the application developer.*
- Sims 2—“Smooth Edges (AA)” option is not available with Release 100 drivers. [272477]
*This occurs because of an incorrect driver version check in the application.
NVIDIA has worked around this issue in the operating system by changing the way the driver version is reported to this application.*
- Warhammer 40k Dawn of War (all versions) does not run with Release 100 drivers. [273154]
*This occurs because of an incorrect driver version check in the application.
NVIDIA has worked around this issue in the operating system by changing the way the driver version is reported to this application.*
- Need for Speed Carbon—After upgrading with patch 1.3, the game crashes when launched. [290506]
This is an issue with the application patch under Windows Vista.
- Nascar Simracing—the game crashes when launched. [270792]
This is an issue with the application under Windows Vista.
- Call of Duty 2—Only solid colors render during game play when 4xAA is enabled. [257454]
*The application is not applying antialiasing properly. Please try selecting 2x AA, disabling antialiasing, or using NVIDIA Enhanced application or Override antialiasing modes.
NVIDIA is pursuing a fix with the application developer*
- Age of Empires III—the game has rendering artifacts, such as textured squares for smoke. [258036]
- Flight Simulator X—pressing Alt+Tab to switch to the desktop does not work. [293729]

- Everquest 2– with NVIDIA driver versions 100.xx, the following error message appears: [273346]

"You currently have a (7.15.11.120) video card installed. We recommend that you download version 7772 drivers before playing Everquest."

This occurs because the application is not checking the driver version correctly, but this does not affect game play. Please select "Continue Anyway" to launch the game. The problem does not occur with a previous Release 95 driver (xx.xx format).

NVIDIA is pursuing a fix with the application developer.

Application Issues Under SLI Mode

- [SLI]: NVIDIA SLI scaling on some applications under Windows Vista may not be as much as under Windows XP. Some applications include "S.T.A.L.K.E.R., Half-Life 2: Lost Coast, Company of Heroes, Battlefield 2142, Call of Duty 2, Hitman: Blood Money, and Far Cry. [302534 290803]

This is an application issue which has been resolved with the latest Steam patch.

Operating System Issues

- World of Warcraft – there is a 60% drop in performance when running the game in windowed mode with SLI or multi-GPU mode enabled. [289427]

This is due to a limitation of the Windows Vista operating system and affects all multi-GPU systems. NVIDIA is investigating a workaround for this performance problem.

CHAPTER

3

THE RELEASE 177 DRIVER

This chapter covers the following main topics:

- “Hardware and Software Support” on page 15
- “Driver Installation” on page 17
- “NVIDIA Driver History” on page 18

Hardware and Software Support

Supported Operating Systems

The Release 177 driver, version 177.41, has been tested with Microsoft Windows® Vista RTM OS builds version 6000 or higher, and supports both 32-bit and 64-bit versions of Windows Vista Editions:

- Windows Vista Home Basic
- Windows Vista Home Premium
- Windows Vista Business
- Windows Vista Enterprise Edition
- Windows Vista Ultimate

Supported NVIDIA Products

Table 3.1 lists the NVIDIA products supported by the Release 177 driver, version 177.41

Table 3.1 Supported NVIDIA Products

Consumer Products

GeForce GTX 280
 GeForce GTX 260
 nForce 780a SLI
 nForce 750a SLI

Supported Languages

The Release 177 Graphics Drivers supports the following languages in the main driver Control Panel:

English (USA)	German	Portuguese (Euro/Iberian)
English (UK)	Greek	Russian
Arabic	Hebrew	Slovak
Chinese (Simplified)	Hungarian	Slovenian
Chinese (Traditional)	Italian	Spanish
Czech	Japanese	Spanish (Latin America)
Danish	Korean	Swedish
Dutch	Norwegian	Thai
Finnish	Polish	Turkish
French	Portuguese (Brazil)	

Driver Installation

Minimum Hard Disk Space

The hard disk space requirement is minimum 38.2 MB for English-only, and 66.4 MB for International.

Before You Begin

If you have previously installed NVIDIA nTune, NVIDIA recommends that you uninstall nTune before installing this driver. After the driver install is complete, you can reinstall NVIDIA nTune.

Installation Instructions

- 1 Follow the instructions on the NVIDIA .com Web site driver download page to locate the appropriate driver to download, based on your hardware and operating system.
- 2 Click the driver download link.
- 3 The license agreement dialog box appears.
- 4 Click **Accept** if you accept the terms of the agreement, then either open the file or save the file to your PC and open it later.
- 5 Extract the zip files to a temporary folder on your PC.
- 6 Open the NVIDIA driver installation .EXE file to launch the NVIDIA InstallShield Wizard.
- 7 Follow the instructions in the NVIDIA InstallShield Wizard to complete the installation.

Note: After the driver installation, Windows may default to 16-bpp color and disable the Desktop Window Manager (DWM). To work around this issue, set the color to 32-bpp and then reboot the PC.

NVIDIA Driver History

Release 177 is the latest NVIDIA driver available. [Table 3.1](#) contains a summary of some previous driver releases and the versions associated with them. Some versions listed may not have been released outside of NVIDIA.

Table 3.1 NVIDIA Drivers for Windows Vista

Windows Vista Build	NVIDIA Graphics Driver
RTM OS Builds 6000 or higher	Release 177: Version 177.35, 177.41
RTM OS Builds 6000 or higher	Release 175: Version 175.12, 175.16, 175.19
RTM OS Builds 6000 or higher	Release 174: Version 174.16, 174.53, 174.74
RTM OS Builds 6000 or higher	Release 169: Version 169.02, 169.04, 169.09, 169.12, 169.13, 169.21, 169.25
RTM OS Builds 6000 or higher	Release 167: Version 167.35
RTM OS Builds 6000 or higher	Release 163: Version 163.11, 163.44, 163.67, 163.69, 163.71, 163.75
RTM OS Builds 6000 or higher	Release 162: Version 162.22
RTM OS Builds 6000 or higher	Release 158: Version 158.14, 158.18, 158.24, 158.42, 158.43, 158.45
RTM OS Builds 6000 or higher	Release 100: Version 100.53, 100.54, 100.59, 100.64, 100.65, 101.41 Release 95: Version 97.46
RC2 OS Builds 5744 or higher	Release 95: Version 96.85
RC1 OS Builds 5520.RC1_16384.060812-2235 or higher	Release 95: Version 96.33
Build 5472.WinMain_idx01_5.060713-1900 or higher	Release 95: Versions 95.60–96.00
Windows Vista Beta2	NVIDIA Driver version 88.61
February 06 CTP build 5308.FebCTP_Final.060217-2200 or higher	NVIDIA Drivers 87.15, 87.45
July 05 Vista Beta1	NVIDIA Driver included 'in the box'.
December 05 CTP build 5270.Winmain.051214-1910	NVIDIA Driver included 'in the box'.

Known Product Limitations

This section describes problems that will not be fixed. Usually, the source of the problem is beyond the control of NVIDIA. Following is the list of problems and where they are discussed in this document:

- “Image Sharpening Control not Available with GeForce 8 Series and later GPUs” on page 20
- “Gigabyte GA-6BX Motherboard” on page 20

Image Sharpening Control not Available with GeForce 8 Series and later GPUs

With GeForce 8 Series and later graphics cards, the **Image sharpening** slider on the NVIDIA Control Panel->Display->Adjust Desktop Color Settings page is grayed out.

This control is intentionally disabled because image sharpening is not supported on GeForce 8 series and later GPUs.

Gigabyte GA-6BX Motherboard

This motherboard uses a Linfinity regulator on the 3.3-V rail that is rated to only 5 A—less than the AGP specification, which requires 6 A. When diagnostics or applications are running, the temperature of the regulator rises, causing the voltage to the NVIDIA chip to drop as low as 2.2 V. Under these circumstances, the regulator cannot supply the current on the 3.3-V rail that the NVIDIA chip requires.

This problem does not occur when the graphics board has a switching regulator or when an external power supply is connected to the 3.3-V rail.

APPENDIX



MODE SUPPORT FOR WINDOWS

This chapter details the Windows modes supported by the Release 177 driver for NVIDIA products. It contains these sections:

- “General Mode Support Information” on page 22
- “Default Modes Supported by GPU” on page 23
- “Modes Supported by TV Encoders” on page 29

General Mode Support Information

The NVIDIA graphics driver includes a standard list of display modes that are supported by default. These modes are listed in the section [“Default Modes Supported by GPU”](#) on page 23.

The actual modes available depend on the capabilities of the display. In addition, the NVIDIA graphics driver has a “dynamic EDID detection” capability and will make available *additional* modes that are listed in the display EDID, provided the graphics hardware can support it.

The NVIDIA graphics driver also supports the high resolutions available with the displays listed in [Table A.1](#) as well as the non-standard modes listed in [Table A.2](#).

Table A.1 Modes Supported for High Resolution Displays

Display	Maximum Resolution	Hardware Requirements
Apple 30" Cinema HD Display (Dual link DVI)	2560x1600 @ 60 Hz	<ul style="list-style-type: none"> • All GeForce 7 series GPUs and later • GeForce 6800 Ultra 512 • GeForce 6800 with 512 MB
Dell WFP 3007 (Dual Link DVI)	2560x1600 @ 60 Hz	
HP LP3065 dual-link DVI flat panel	2560x1600 @ 60Hz.	

Table A.2 Non-standard Modes Supported

Resolution
1680 x 1050
1366 x 768

Default Modes Supported by GPU

This section lists the modes that are included by default in the driver INF for the following product families:

- “GeForce 200 Series of GPUs” on page 24
- “nForce 7xx Series” on page 26

Understanding the Mode Format

Figure A.1 gives an example of how to read the mode information presented in this section.

Resolution	Color Depth	Refresh Rates
1024 x 768	32	60 70 72 75 85 100 120 140 144 150 170 200

Example entry:

Meaning:

Resolution:	1024 x 768
Color depth:	32 bpp
Refresh rates:	60 Hz, 70 Hz, 72 Hz, 75 Hz, 85 Hz, 100 Hz, 120 Hz, 140 Hz, 144 Hz, 150 Hz, 170 Hz, and 200 Hz

Figure A.1 Mode Format

Note:

- Horizontal spanning modes of 3840x1080 and above, and vertical spanning modes of 1920x2160 and above generally require at least 32 MB of video memory at 32 bpp.
- An “i” next to the refresh rate indicates an interlaced refresh rate.

GeForce 200 Series of GPUs

This sections lists the supported display resolutions, color depths, and refresh rates for the following products:

- NVIDIA GeForce GTX 280
- NVIDIA GeForce GTX 260

Standard Modes

640 x 480	8	60
800 x 600	8	60 70 75 85 100
848 x 480	8	60 70 75 85 100
960 x 600	8	60 70 75 85 100
1024 x 768	8	60 70 75 85 100
1152 x 864	8	60 70 75 85 100
1280 x 768	8	60
1280 x 800	8	60
1280 x 960	8	60 70 75 85 100
1280 x 1024	8	60 70 75 85 100
1360 x 768	8	60
1600 x 1200	8	60 70 75 85 100
1680 x 1050	8	60
1920 x 1200	8	60
1920 x 1440	8	60 70 75 85 100
2048 x 1536	8	60 70 75 85 100

640 x 480	16	60
800 x 600	16	60 70 75 85 100
848 x 480	16	60 70 75 85 100
960 x 600	16	60 70 75 85 100
1024 x 768	16	60 70 75 85 100
1152 x 864	16	60 70 75 85 100
1280 x 768	16	60
1280 x 800	16	60
1280 x 960	16	60 70 75 85 100
1280 x 1024	16	60 70 75 85 100
1360 x 768	16	60
1600 x 1200	16	60 70 75 85 100

1680 x 1050	16	60					
1920 x 1200	16	60					
1920 x 1440	16	60	70	75	85	100	
2048 x 1536	16	60	70	75	85	100	

640 x 480	32	60					
800 x 600	32	60	70	75	85	100	
848 x 480	32	60	70	75	85	100	
960 x 600	32	60	70	75	85	100	
1024 x 768	32	60	70	75	85	100	
1152 x 864	32	60	70	75	85	100	
1280 x 768	32	60					
1280 x 800	32	60					
1280 x 960	32	60	70	75	85	100	
1280 x 1024	32	60	70	75	85	100	
1360 x 768	32	60					
1600 x 1200	32	60	70	75	85	100	
1680 x 1050	32	60					
1920 x 1200	32	60					
1920 x 1440	32	60	70	75	85	100	
2048 x 1536	32	60	70	75	85	100	

640 x 480	64	60					
800 x 600	64	60	70	75	85	100	
848 x 480	64	60	70	75	85	100	
960 x 600	64	60	70	75	85	100	
1024 x 768	64	60	70	75	85	100	
1152 x 864	64	60	70	75	85	100	
1280 x 768	64	60					
1280 x 800	64	60					
1280 x 960	64	60	70	75	85	100	
1280 x 1024	64	60	70	75	85	100	
1360 x 768	64	60					
1600 x 1200	64	60	70	75	85	100	
1680 x 1050	64	60					
1920 x 1200	64	60					
1920 x 1440	64	60	70	75	85	100	
2048 x 1536	64	60	70	75	85	100	

nForce 7xx Series

This sections lists the supported display resolutions, color depths, and refresh rates for the following products:

- NVIDIA nForce 780a SLI
- NVIDIA nForce 750a SLI

Standard Modes

640 x 480	8		60 70 72 75 85 100 120 140 144 150 170 200 240
800 x 600	8		60 70 72 75 85 100 120 140 144 150 170 200 240
848 x 480	8		60 70 72 75 85 100 120 140 144 150 170 200 240
960 x 600	8		60 70 72 75 85 100 120 140 144 150 170 200 240
1024 x 768	8		60 70 72 75 85 100 120 140 144 150 170 200 240
1152 x 864	8		60 70 72 75 85 100 120 140 144 150 170 200
1280 x 720	8		60 70 72 75 85 100 120 140 144 150 170
1280 x 768	8		60 70 72 75 85 100 120 140 144 150 170
1280 x 800	8		60 70 72 75 85 100 120 140 144 150 170
1280 x 960	8		60 70 72 75 85 100 120 140 144 150 170
1280 x 1024	8		60 70 72 75 85 100 120 140 144 150 170
1360 x 768	8		60 70 72 75 85 100 120 140 144 150 170
1440 x 900	8		60 70 72 75 85 100 120 140 144 150 170 200
1600 x 1200	8		60 70 72 75 85 100 120
1680 x 1050	8		60
1920 x 1080	8	30i	60 70 72 75 85 100
1920 x 1200	8		60 70 72 75 85 100
1920 x 1440	8		60 70 72 75 85
2048 x 1536	8		60 70 72 75 85

640 x 480	16		60 70 72 75 85 100 120 140 144 150 170 200 240
800 x 600	16		60 70 72 75 85 100 120 140 144 150 170 200 240
848 x 480	16		60 70 72 75 85 100 120 140 144 150 170 200 240
960 x 600	16		60 70 72 75 85 100 120 140 144 150 170 200 240
1024 x 768	16		60 70 72 75 85 100 120 140 144 150 170 200 240
1152 x 864	16		60 70 72 75 85 100 120 140 144 150 170 200
1280 x 720	16		60 70 72 75 85 100 120 140 144 150 170
1280 x 768	16		60 70 72 75 85 100 120 140 144 150 170
1280 x 800	16		60 70 72 75 85 100 120 140 144 150 170
1280 x 960	16		60 70 72 75 85 100 120 140 144 150 170
1280 x 1024	16		60 70 72 75 85 100 120 140 144 150 170

1360 x 768	16		60 70 72 75 85 100 120 140 144 150 170
1440 x 900	16		60 70 72 75 85 100 120 140 144 150 170 200
1600 x 1200	16		60 70 72 75 85 100 120
1680 x 1050	16		60
1920 x 1080	16	30i	60 70 72 75 85 100
1920 x 1200	16		60 70 72 75 85 100
1920 x 1440	16		60 70 72 75 85
2048 x 1536	16		60 70 72 75 85

640 x 480	32		60 70 72 75 85 100 120 140 144 150 170 200 240
800 x 600	32		60 70 72 75 85 100 120 140 144 150 170 200 240
848 x 480	32		60 70 72 75 85 100 120 140 144 150 170 200 240
960 x 600	32		60 70 72 75 85 100 120 140 144 150 170 200 240
1024 x 768	32		60 70 72 75 85 100 120 140 144 150 170 200
1152 x 864	32		60 70 72 75 85 100 120 140 144 150 170 200
1280 x 720	32		60 70 72 75 85 100 120 140 144 150
1280 x 768	32		60 70 72 75 85 100 120 140 144 150
1280 x 800	32		60 70 72 75 85 100 120 140 144 150
1280 x 960	32		60 70 72 75 85 100 120 140 144 150
1280 x 1024	32		60 70 72 75 85 100 120 140 144 150
1360 x 768	32		60 70 72 75 85 100 120 140 144 150
1440 x 900	32		60 70 72 75 85 100 120 140 144 150 170 200
1600 x 1200	32		60 70 72 75 85 100
1680 x 1050	32		60
1920 x 1080	32	30i	60 70 72 75 85
1920 x 1200	32		60 70 72 75 85
1920 x 1440	32		60 70 72 75 85
2048 x 1536	32		60 70 72 75 85

640 x 480	64		60 70 72 75 85 100 120 140 144 150 170 200 240
800 x 600	64		60 70 72 75 85 100 120 140 144 150 170 200 240
848 x 480	64		60 70 72 75 85 100 120 140 144 150 170 200 240
960 x 600	64		60 70 72 75 85 100 120 140 144 150 170 200 240
1024 x 768	64		70
1152 x 864	64		60 70 72 75 85 100 120 140 144 150 170 200
1280 x 720	64		70
1280 x 768	64		60 70 72 75 85 100
1280 x 800	64		60 70 72 75 85 100
1280 x 960	64		60 70 72 75 85 100

1280 x 1024	64		60 70 72 75 85 100
1360 x 768	64		60 70 72 75 85 100
1440 x 900	64		60 70 72 75 85 100 120 140 144 150 170 200
1600 x 1200	64		60 70 72 75 85 100
1680 x 1050	64		60
1920 x 1080	64	30i	
1920 x 1200	64		70
1920 x 1440	64		60 70 72 75 85
2048 x 1536	64		60 70 72 75 85

Modes Supported by TV Encoders

Table A.3 and Table A.4 list the NTSC, PAL, and HDTV TV-Out modes supported by the NVIDIA driver.

Table A.3 Mode Support for S-Video and Composite Out

Resolution	Bit depth	Comments
320x200	8, 16, 32	DirectDraw mode; not selectable as a Windows desktop
320x240	8, 16, 32	DirectDraw mode; not selectable as a Windows desktop
640x400	8, 16, 32	DirectDraw mode; not selectable as a Windows desktop
640x480	8, 16, 32	
720x480	8, 16, 32	Overscans (for video)
720x576	8, 16, 32	Overscans (for video)
800x600	8, 16, 32	
1024x768	8, 16, 32	Conexant 25871 only

Table A.4 Mode Support for Component YPrPb Out and DVI Out

Resolution	Comments
480i (SDTV)	Supported on graphics boards with Conexant 875 or Philips 7108 TV encoders and compatible connectors, and compatible GeForce 6 Series and GeForce 7 Series GPUs.
480p (EDTV)	
720p (HDTV)	
1080i (HDTV)	
576i (PAL)	
576p (PAL)	

The driver supports manual overscan correction for component and DVI outputs. See the NVIDIA Control Panel online help for instructions on how to use the overscan correction features in the control panel.